



S-470 OO  
GENERAL PURPOSE S&D - PVC  
FDA

TUBE : TRASPARENT PVC - ABRASION AND OZONE RESISTANT  
 REINFORCEMENT : STEEL HELIX WIRE  
 COVER :  
 APPLICATION : GENERAL PURPOSE WATER AND LIQUIDS SUCTION AND DELIVERY. STERILIZE WITH 5% SODA SOLUTION.  
 SAFETY FACTOR : 3:1  
 TEMPERATURE : -5°C +60°C (+23°F +140°F)  
 BRAND TEXT : ALFAGOMMA - ITALY - S-470 - GENERAL PURPOSE -FDA -lotto  
 BRAND TYPE : BLACK LETTERS  
 APPROVALS :  
 NOTE :

Code	ID mm	ID inch	OD mm	Wall mm	Weight g/m	WP bar	WP psi	Vac. %	BR mm	Available Length m	Stock Length m
<a href="#">47000010164LK0</a>	10	3/8	16	3	170	15	225	90	40	60	60
<a href="#">47000013194LK0</a>	13	1/2	19	3	205	7	100	85	52	60	60
<a href="#">47000014204LK0</a>	14	9/16	20	3	220	6	90	85	56	60	60
<a href="#">47000016224LK0</a>	16	5/8	22	3	250	6	90	85	64	60	60
<a href="#">47000018264LK0</a>	18	23/32	26	4	320	6	90	85	72	60	60
<a href="#">47000020284LK0</a>	20	13/16	28	4	340	5	75	85	80	60	60
<a href="#">47000022304LK0</a>	22	7/8	30	4	380	5	75	85	88	60	60
<a href="#">47000025334LK0</a>	25	1"	33	4	530	5	75	85	100	60	60
<a href="#">47000030384LK0</a>	30	1" 3/16	38	4	620	4	60	85	120	60	60
<a href="#">47000032404LK0</a>	32	1" 1/4	40	4	655	4	60	85	128	60	60
<a href="#">47000035454LK0</a>	35	1" 3/8	45	5	800	4	60	85	140	60	60
<a href="#">47000038484LK0</a>	38	1" 1/2	48	5	855	4	60	85	152	30	30
<a href="#">47000040504LK0</a>	40	1" 9/16	50	5	895	3	45	85	160	30	30
<a href="#">47000045554LK0</a>	45	1" 3/4	55	5	1100	3	45	80	180	30	30
<a href="#">47000051614LK0</a>	51	2"	61	5	1230	3	45	80	204	30	30
<a href="#">47000060724LK0</a>	60	2" 3/8	72	6	1700	2	30	80	240	30	30
<a href="#">47000063754LK0</a>	63	2" 1/2	75	6	1775	2	30	80	252	30	30
<a href="#">47000070844LK0</a>	70	2" 3/4	84	7	2030	2	30	80	280	30	30
<a href="#">47000076904LK0</a>	76	3"	90	7	2450	2	30	70	304	30	30
<a href="#">47000080944LK0</a>	80	3" 1/8	94	7	2565	2	30	70	320	30	30
<a href="#">47000090044LK0</a>	90	3" 1/2	104	7	3000	2	30	70	360	30	30
<a href="#">47000102164LK0</a>	102	4"	116	7	3480	2	30	70	408	30	30
<a href="#">47000105214LK0</a>	105	4" 1/8	121	8	4250	3	45	90	420	2,8	2,8
<a href="#">47000152724LK0</a>	152	6"	172	10	7300	2	30	70	608	20	20